

EZ-Swivel® Couplers

Customer satisfaction is the main priority under the Beyes quality policy. EZ-Swivel Couplers have been developed, manufactured and subjected to final inspection according to legal regulations, quality norms and industry standards.

KEY SPECIFICATION

Hose Type	ISO 9168 type 1, ISO 9168 type 3
Recommended Voltage Range	3.2 ± 0.1 V AC/DC
Temperature for Storage	-40 °C to +70 °C (-40 °F to +158 °F)
Air humidity for storage	8 % to 80 % (relative), non-condensing
Ambient temperature during operation	+10 °C to +35 °C (+50 °F to +86 °F)
Air humidity during operation	15 % to 80 % (relative), non-condensing

ORDER INFORMATION

QD Couplers



4 Holes
Code: HP3018
Model: EZ-Swivel QD M4

2 Holes
Code: HP3019
Model: EZ-Swivel QD B2

PD Couplers



4 Holes
Code: HP6008
Model: EZ-Swivel PD M4

2 Holes
Code: HP6002
Model: EZ-Swivel PD B2

K Couplers



4 Holes
Code: HP2063
Model: EZ-Swivel K M4

2 Holes
Code: HP2064
Model: EZ-Swivel K E6

Beyes
The Next Standard®

Beyes Dental Canada Inc.
23-595 Middlefield Road
Toronto, Ontario, M1B 3M5
Canada
Tel: 1-855-603-1888
Email: info@beyes.ca
Web: www.beyes.ca

EU REP

Lotus NL B.V.
Koningin Julianaplein 10, Ie Verd,
2595AA, The Hague,
Netherlands
Tel: +31645171879 (English)
+31626669008 (Dutch)
Web: www.beyes.ca

Your Dealer for Beyes Products

Scan the QR code for more information



Printed in Canada
File #: EN8032
Rev.1 / 06.11.20

© Beyes Canada Inc 2020. All Rights Reserved.
Specifications are subject to change without notice.
All brands are holders of their respective trademarks.
All Beyes products are manufactured in strict compliance with Health Canada regulations ensuring quality.
Manufacturing facility is ISO 13485 certified under Canadian Medical Devices Conformity Assessment System (CMDCAS).